Introduction to MPLS

Tor Skeie

University of Oslo, Department of informatics

This presentation is based mainly on Santanu Dasgupta´s slide series that describe the Multiprotocol Label Switching (MPLS) concept

Santanu Dasgupta is a Distinguished Architect at Cisco




UiO : University of Oslo


© 2010 Cisco and/or its affiliates. All rights reserved.

Theory

ISO/OSI model




DoD model



© 2010 Cisco and/or its affiliates. All rights reserved.

Reality



Typical packet from AT&T backbone network

Pamela Zave and Jennifer Rexford. 2019. The compositional architecture of the internet. Commun. ACM 62, 3 (February 2019), 78-87. DOI: https://doi.org/10.1145/3226588

© 2010 Cisco and/or its affiliates. All rights reserved.

Goals of this Lecture

- Understand the business drivers for MPLS
  - Understand the problems MPLS is addressing, herein learn about MPLS customer and market segments
  - Understand benefits of deploying MPLS
- Understand the major MPLS technology components
- Understand typical applications of MPLS

© 2010 Cisco and/or its affiliates. All rights reserved.


Agenda

- Introduction
- MPLS Network Components → **Core MPLS**
- MPLS Traffic Engineering → **MPLS Network Services**
- MPLS VPNs
  - MPLS Layer-3 VPNs
  - MPLS Layer-2 VPNs


  → **End-to-end MPLS Services**
- Summary

© 2010 Cisco and/or its affiliates. All rights reserved.

Introduction



The Big Picture



© 2010 Cisco and/or its affiliates. All rights reserved.

Why Multi Protocol Label Switching?

- SP/Carrier perspective
  - Reduce costs (CAPEX); consolidate networks
  - Consolidated network for multiple Layer-2/3 services
  - Support increasingly stringent SLAs
  - Handle increasing scale/complexity of IP-based services
- Enterprise/end-user perspective
  - Campus/LAN
    - Need for network segmentation (users, applications, etc.)
  - WAN connectivity (connecting enterprise networks)
    - Need for easier configuration of site-to-site WAN connectivity

© 2010 Cisco and/or its affiliates. All rights reserved.


What Is MPLS Technology?

- It's all about labels …
- Use the best of both worlds
  - Layer-2 (ATM/FR): efficient forwarding and traffic engineering
  - Layer-3 (IP): flexible and scalable
- MPLS forwarding plane
  - Use of labels for forwarding Layer-2/3 data traffic
  - Labeled packets are being switched instead of routed
    - Leverage layer-2 forwarding efficiency
- MPLS control/signaling plane
  - Use of existing IP control protocols extensions + new protocols to exchange label information
    - Leverage layer-3 control protocol flexibility and scalability

© 2010 Cisco and/or its affiliates. All rights reserved.

Evolution of MPLS

- Evolved from tag switching in 1996 to full IETF standard, covering over 130 RFCs
- Key application initially were Layer-3 VPNs, followed by Traffic Engineering (TE), and Layer-2 VPNs



© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Applications



For your reference only


	Service Providers	Enterprise Data Center	Data center interconnects	EWAN Edge
Key Features	L2/L3VPN's TE/FRR QoS High Availability	VPN's TE/FRR High Availability	VPN's / VRF's VRF-Aware Security High Availability	VPN's / VRF's VRF Aware Security High Availability
Applications	Hosted Data centers Data center interconnect Segmentation for IT Mergers, Acquisitions, spinoffs	Departmental segmentation Service multiplexing Security Mergers, Acquisitions, spinoffs	Disaster Recovery Vmotion support Branch Interconnects	Internet Access Branch Connectivity

- **Network Consolidation** – Merging Multiple parallel network into a shared infrastructure
- **Network segmentation** – By user groups or business function
- **Service and policy centralization** – Security policies and appliances at a central location
- **New applications readiness** – Converged multi-service network
- **Increased network security** – User groups segmentation with VPNs

© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS Technology Components

Basic building blocks of MPLS



MPLS Forwarding and Signaling

- MPLS label forwarding and signaling mechanisms




© 2010 Cisco and/or its affiliates. All rights reserved.

Basic Building Blocks

- The big picture
  - MPLS-enabled network devices
  - Label Switched Paths (LSPs)
- The internals
  - MPLS labels
  - Processing of MPLS labels
  - Exchange of label mapping information
  - Forwarding of labeled packets
- Other related protocols to exchange label information
  - Between MPLS-enabled devices

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Network Overview




- P (Provider) router = label switching router = core router (LSR)
  - Switches MPLS-labeled packets
- PE (Provider Edge) router = edge router (LSR)
  - Imposes and removes MPLS labels
- CE (Customer Edge) router
  - Connects customer network to MPLS network

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Label and Label Encapsulation

MPLS Label



COS/EXP = Class of Service: 3 Bits; S = Bottom of Stack; TTL = Time to Live

MPLS Label Encapsulation

PPP Header (Packet over SONET/SDH)




One or More Labels Appended to the Packet (Between L2/L3 packet header and link layer header)

LAN MAC Label Header



© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Label Operations



- Label imposition (Push)

  By ingress PE router; classify and label packets

- Label swapping or switching

  By P router; forward packets using labels; indicates service class & destination

- Label disposition (PoP)

  By egress PE router; remove label and forward original packet to destination CE

© 2010 Cisco and/or its affiliates. All rights reserved.

Forwarding Equivalence Class

- Mechanism to map ingress layer-2/3 packets onto a Label Switched Path (LSP) by ingress PE router
  - Part of label imposition (Push) operation
- Variety of FEC mappings possible
  - IP prefix/host address
  - Groups of addresses/sites (VPN x)
    - Used for L3VPNs
  - Layer 2 circuit ID (ATM, FR, PPP, HDLC, Ethernet)
    - Used for Pseudowires (L2VPNs)
  - Tunnel interface
    - Used for MPLS traffic engineering (TE)

© 2010 Cisco and/or its affiliates. All rights reserved.


Label Distribution Protocol

- MPLS nodes need to exchange label information with each other
  - Ingress PE node (Push operation)
    - Needs to know what label to use for a given FEC to send packet to neighbor
  - Core P node (Swap operation)
    - Needs to know what label to use for swap operation for incoming labeled packets
  - Egress PE node (Pop operation)
    - Needs to tell upstream neighbor what label to use for specific FEC type LDP used for exchange of label (mapping) information
- Label Distribution Protocol (LDP)
  - Defined in RFC 3035 and RFC3036; updated by RFC5036
  - LDP is a superset of the Cisco-specific Tag Distribution Protocol
- Note that, in addition LDP, also other protocols are being used for label information exchange
  - Will be discussed later

© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS Control and Forwarding Plane

- MPLS control plane
  - Used for distributing labels and building label-switched paths (LSPs)
  - Typically supported by LDP; also supported via RSVP and BGP
  - Labels define destination and service
- MPLS forwarding plane
  - Used for label imposition, swapping, and disposition
  - Independent of type of control plane
  - Labels separate forwarding from IP address-based routing
  - MFI – MPLS Forwarding Infrastructure




© 2010 Cisco and/or its affiliates. All rights reserved.

IP Packet Forwarding Example




© 2010 Cisco and/or its affiliates. All rights reserved.

Step 1: IP Routing (IGP) Convergence




© 2010 Cisco and/or its affiliates. All rights reserved.

Step 2a: LDP Assigns Local Labels




© 2010 Cisco and/or its affiliates. All rights reserved.

Step 2b: LDP Assigns Remote Labels



© 2010 Cisco and/or its affiliates. All rights reserved.

Step 3: Forwarding MPLS Packets



© 2010 Cisco and/or its affiliates. All rights reserved.


Summary Steps For MPLS Forwarding

- Each node maintains IP routing information via IGP (Interior Gateway Protocol)
  - IP routing table (RIB) and IP forwarding table (FIB)
- LDP leverages IGP routing information
- LDP label mapping exchange (between MPLS nodes) takes place after IGP has converged
  - LDP depends on IGP convergence
  - Label binding information stored in LIB
- Once LDP has received remote label binding information MPLS forwarding is updated
  - Label bindings are received from remote LDP peers
  - MPLS forwarding via MFI (MPLS Forwarding Infrastructure)

© 2010 Cisco and/or its affiliates. All rights reserved.


Label Stacking

- More than one label can be used for MPLS packet encapsulation
  - Creation of a label stack
- Recap: labels correspond to Forwarding Equivalence Class (FEC)
  - Each label in stack used for different purposes
- Outer label always used for switching MPLS packets in network
- Remaining inner labels used to specific services/FECs, etc.
- Last label in stack marked with EOS bit
- Allows building services such as
  - MPLS VPNs; LDP + VPN label
  - Traffic engineering (FRR): LDP + TE label
  - VPNs over TE core: LDP + TE + VPN label
  - Any transport over MPLS: LDP + PW label



© 2010 Cisco and/or its affiliates. All rights reserved.


Scalability through label stacking



Tunnel label determines the path to remote edge
VC label designates connection at tunnel endpoint

© 2010 Cisco and/or its affiliates. All rights reserved.

Scalability through label stacking




Tunnel label determines the path to remote edge
VC label designates connection at tunnel endpoint

© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS Traffic Engineering

Technology Overview and Applications



MPLS Technology Framework

- Traffic engineering capabilities for bandwidth management and network failure protection



© 2010 Cisco and/or its affiliates. All rights reserved.

Why Traffic Engineering?

- Congestion in the network due to changing traffic patterns
  - Election news, online trading, major sports events
- Better utilization of available bandwidth
  - Route on the non-shortest path
- Route around failed links/nodes
  - Fast rerouting around failures, transparently to users
  - Like SONET APS (Automatic Protection Switching)
- Build new services—virtual leased line services
  - VoIP toll-bypass applications, point-to-point bandwidth guarantees
- Capacity planning
  - TE improves aggregate availability of the network

© 2010 Cisco and/or its affiliates. All rights reserved.


The Problem with Shortest-Path

IP (Mostly) Uses Destination-Based Least-Cost Routing
Alternate Path Under Utilized

Node	Next-Hop	Cost
B	B	10
C	C	10
D	C	20
E	B	20
F	B	30
G	B	30

- Some links are DS3 (45 Mbps), some are OC-3 (155 Mbps)
- Router A has 40M of traffic for router F, 40M of traffic for router G
- Massive (44%) packet loss at router B→router E!

Changing to A->C->D->E won't help




© 2010 Cisco and/or its affiliates. All rights reserved.

How MPLS TE Solves the Problem


Node	Next-Hop	Cost
B	B	10
C	C	10
D	C	20
E	B	20
F	Tunnel 0	30
G	Tunnel 1	30

- Router A sees all links
- Router A computes paths on properties other than just shortest cost; creation of 2 tunnels
- No link oversubscribed!



© 2010 Cisco and/or its affiliates. All rights reserved.

How MPLS TE Works




- Link information Distribution*
  - ISIS-TE
  - OSPF-TE
- Path Calculation (CSPF)*
- Path Setup
- Forwarding Traffic down Tunnel
  - Auto-route
  - Static
  - PBR
  - CBTS / PBTS
  - Forwarding Adjacency
  - Tunnel select

*** Optional**

© 2010 Cisco and/or its affiliates. All rights reserved.


Path Calculation



- TE nodes can perform constraint-based routing
- Constraints and topology database as input to path computation
- Shortest-path-first algorithm ignores links not meeting constraints
- Tunnel can be signaled once a path is found
- Not required if using offline path computation

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS TE FRR - Link Protection



- Primary tunnel: A → B → D → E
- Backup tunnel: B → C → D (preprovisioned)
- Recovery = ~ 50 ms


*Actual Time Varies—Well Below 50 ms in Lab Tests, Can Also Be Higher

© 2010 Cisco and/or its affiliates. All rights reserved.

Use Case 1: Tactical TE Deployment

Requirement: Need to Handle Scattered Congestion Points in the Network

Solution: Deploy MPLS TE on Only Those Nodes that Face Congestion




© 2010 Cisco and/or its affiliates. All rights reserved.

Use Case 2: 1-Hop Tunnel Deployment

Requirement: Need Protection Only — Minimize Packet Loss of Bandwidth in the Core

Solution: Deploy MPLS Fast Reroute for Less than 50ms Failover Time with 1-Hop Primary TE Tunnels and Backup Tunnel for Each



© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS TE Summary

- MPLS TE can be used to implement traffic engineering to enable enhanced network availability, utilization, and performance
- Enhanced network availability can be implemented via MPLS TE Fast Re-Route (FRR)
  - Link, node, and path protection
  - Automatically route around failed links/nodes; like SONET APS
- Better network bandwidth utilization can be implemented via creation of MPLS TE tunnels using explicit routes
  - Route on the non-shortest path
- MPLS TE can be used for capacity planning by creation of bandwidth-specific tunnels with explicit paths through the network
  - Bandwidth management across links and end-to-end paths

© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS VPNs

Overviews



MPLS Technology Framework

- End-to-end data connectivity services across MPLS networks (from PE to PE)




© 2010 Cisco and/or its affiliates. All rights reserved.

What Is a Virtual Private Network?

- VPN is a set of sites or groups which are allowed to communicate with each other in a secure way
  - Typically over a shared public or private network infrastructure
- VPN is defined by a set of administrative policies
  - Policies established by VPN customers themselves (DIY)
  - Policies implemented by VPN service provider (managed/unmanaged)
- Different inter-site connectivity schemes possible
  - Ranging from complete to partial mesh, hub-and-spoke
- Sites may be either within the same or in different organizations
  - VPN can be either intranet or extranet
- Site may be in more than one VPN
  - VPNs may overlap
- Not all sites have to be connected to the same service provider
  - VPN can span multiple providers

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS VPN Example



- PE-CE link

  Connect customer network to SP network; layer-2 or layer-3


- VPN

  Dedicated secure connectivity over shared infrastructure

© 2010 Cisco and/or its affiliates. All rights reserved.

VPN Route Distribution

Exchange of VPN Policies among PE Routers




- Full mesh of BGP sessions among all PE routers
  - Multi-Protocol BGP extensions (MP-iBGP)
  - Typically BGP Route Reflector (RR) used for improved scalability

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS VPN Example

Basic Building Blocks

- **VPN policies**
  - Configured on PE routers (manual operation)
- **VPN signalling**
  - Between PEs
  - Exchange of VPN policies
- **VPN traffic forwarding**
  - Additional VPN-related MPLS label encapsulation
- **PE-CE link**
  - Connects customer network to MPLS network; either layer-2 or layer-3




© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS VPN Benefits

- SP/Carrier perspective
  - Reduce costs (CAPEX)
    - Leverage same network for multiple services and customers
    - Migrate legacy networks onto single converged network
  - Reduce costs (OPEX)
    - Easier service enablement; only edge node configuration
- Enterprise/end-user perspective
  - Enables site/campus network segmentation
    - Allows for dedicated connectivity for users, applications, etc.
  - Enables easier setup of WAN connectivity
    - Easier configuration of site-to-site WAN connectivity (for L3VPN); only one WAN connection needed

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS VPN Options



- CE connected to PE via p2p Layer-2 connection (FR, ATM)
- CEs peer with each other (IP routing) via p2p layer-2 VPN connection
- CE-CE routing; no SP involvement


- CE connected to PE via Ethernet connection (VLAN)
- CEs peer with each other via fully/partial mesh Layer-2 VPN connection
- CE-CE routing; no SP involvement

- CE connected to PE via IP-based connection (over any layer-2 type)
  - Static routing
  - PE-CE routing protocol; eBGP, OSPF, IS-IS
- CEs peer with PE router
- PE routers maintain customer-specific routing tables and exchange customer=specific routing information
- Layer-3 VPN provider's PE routers are part of customer routing

© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Layer-3 VPNs


Technology Overview and Applications



MPLS Layer-3 Virtual Private Networks

Topics

- Technology components
- VPN control plane mechanisms
- VPN forwarding plane
- Deployment use cases
  - Business VPN services
  - Network segmentation
  - Data Centre access




© 2010 Cisco and/or its affiliates. All rights reserved.

Virtual Routing and Forwarding Instance - VRF


Virtual Routing Table and Forwarding Separate to Customer Traffic

- Logical routing context within the same PE device
- Unique to a VPN
- Allows for customer overlapping IP addresses
- Deployment use cases
  - Business VPN services
  - Network segmentation
  - Data Centre access



© 2010 Cisco and/or its affiliates. All rights reserved.


Virtual Routing and Forwarding Instance



- Typically one VRF created for each customer VPN on PE router
- VRF associated with one or more customer interfaces
- VRF has its own instance of routing table (RIB) and forwarding table (CEF)
- VRF has its own instance for PE-CE configured routing protocols

© 2010 Cisco and/or its affiliates. All rights reserved.

VPN Control Plane Processing



Make customer routes unique:

- Route Distinguisher (RD): 8-byte field, VRF parameters; unique value assigned by a provider to each VPN to make different VPN routes unique
- VPNv4 address: RD+VPN IP prefix

Selective distribute customer routes:


- Route Target (RT): 8-byte field, VRF parameter, unique value to define the import/export rules for VPNv4 routes
- MP-iBGP: advertises VPNv4* prefixes + labels

Processing Steps:

1. CE1 redistribute IPv4 route to PE1 via eBGP.
2. PE1 allocates VPN label for prefix learnt from CE1 to create unique VPNv4 route
3. PE1 redistributes VPNv4 route into MP-iBGP, it sets itself as a next hop and relays VPN site routes to PE2
4. PE2 receives VPNv4 route and, via processing in local VRF (green), it redistributes original IPv4 route to CE2.

© 2010 Cisco and/or its affiliates. All rights reserved.

VPN Forwarding Plane Processing



Processing Steps:


1. CE2 forwards IPv4 packet to PE2.
2. PE2 imposes pre-allocated VPN label (learned via MP-IBGP) to IPv4 packet received from CE2.
3. PE2 imposes outer IGP label (learned via LDP) and forwards labeled packet to next-hop P-router P2.
4. P-routers P1 and P2 swap outer IGP label and forward label packet to PE1.
5. Router PE1 strips VPN label and forwards IPv4 packet to CE1.

© 2010 Cisco and/or its affiliates. All rights reserved.

Use Case 1: Traffic Separation

Requirement: Need to ensure data separation between Aerospace, Cosmetics and Financial Services, while leveraging a shared infrastructure

Solution: Create MPLS VPN for each group




© 2010 Cisco and/or its affiliates. All rights reserved.

Use Case 2: Simplify Hub Site Design

Requirement: To ease the scale and design of head-end site

Solution: Implement MPLS Layer 3 VPNs, which reduces the number of routing peers of the central site



© 2010 Cisco and/or its affiliates. All rights reserved.


MPLS Layer-3 VPN Summary

- Provide layer-3 connectivity among customer sites via Layer-3 VPN (and across PE-CE link)
- Implemented via VRFs on edge/PE nodes providing customer route and forwarding segmentation
- BGP used for control plane to exchange customer VPN (VPNv4) routes between PE routers
- MPLS VPNs enable full-mesh, hub-and-spoke, and hybrid IP connectivity among connected CE sites


© 2010 Cisco and/or its affiliates. All rights reserved.

MPLS Layer-2 VPNs

Technology Overview and Applications




L2VPN Options



© 2010 Cisco and/or its affiliates. All rights reserved.

Layer-2 VPN Overview


- Enables transport of any Layer-2 traffic over MPLS network
  - Includes label encapsulation and translation



© 2010 Cisco and/or its affiliates. All rights reserved.

Any Transport over MPLS Architecture

- Based on IETF's Pseudo-Wire (PW) Reference Model
- PW is a connection (tunnel) between 2 PE Devices, which connects 2 PW End-Services
  - PW connects 2 Attachment Circuits (ACs)
  - Bi-directional (for p2p connections)
  - Use of PW/VC label for encapsulation




© 2010 Cisco and/or its affiliates. All rights reserved.

AToM Technology Components

- PE-CE link
  - Referred to as Attachment Circuit (AC)
  - Can be any type of layer-2 connection (e.g., FR, Ethernet)
- AToM Control Plane
  - Targeted LDP (Label Distribution Protocol) Session
    - Virtual Connection (VC)-label negotiation, withdrawal, error notification
- AToM Forwarding Plane
  - 2 labels used for encapsulation
  - Outer tunnel (LDP) label
    - To get from ingress to egress PE using MPLS LSP
  - Inner de-multiplexer (VC) label
    - To identify L2 circuit (packet) encapsulated within tunnel label

© 2010 Cisco and/or its affiliates. All rights reserved.

AToM Control Plane Processing




Processing Steps (for both P1 and P2):

1. CE1 and CE2 are connected to PE routers via layer-2 connections
2. Via CLI, a new virtual circuit cross-connect is configured, connecting customer interface to manually provided VC ID with target remote PE
3. New targeted LDP session between PE routers established, in case one does not already exist
4. PE binds VC label with customer layer-2 interface and sends label-mapping message to remote PE over LDP session
5. Remote PE receives LDP label binding message and matches VC ID with local configured cross-connect

© 2010 Cisco and/or its affiliates. All rights reserved.

AToM Forwarding Plane Processing



Processing Steps:

1. CE2 forwards layer-2 packet to PE2.
2. PE2 imposes VC (inner) label to layer-2 packet received from CE2 and optionally a control word as well (not shown).
3. PE2 imposes Tunnel outer label and forwards packet to P2.
4. P2 and P1 router forwards packet using outer (tunnel) label.
5. Router PE1 strips Tunnel label and, based on VC label, layer-2 packet is forwarded to customer interface to CE1, after VC label is removed


   In case control word is used, new layer-2 header is generated first.

© 2010 Cisco and/or its affiliates. All rights reserved.

Use Case: L2 Network Interconnect

Requirement: Need to create connectivity between remote customer sites, currently interconnected via Frame Relay WAN connectivity. Only point-to-point connectivity required.

Solution: Interconnect AToM PW between sites, enabling transparent Frame Relay WAN connectivity.



© 2010 Cisco and/or its affiliates. All rights reserved.

Layer-2 VPN Summary

- Enables transport of any Layer-2 traffic over MPLS network
- Two types of L2 VPNs; AToM for point-to-point and VPLS point-to-multipoint layer-2 connectivity
- Layer-2 VPN forwarding based on Pseudo Wires (PW), which use VC label for L2 packet encapsulation

  LDP used for PW signaling
- AToM PWs suited for implementing transparent point-to-point connectivity between Layer-2 circuits

© 2010 Cisco and/or its affiliates. All rights reserved.