NORSK REGNESENTRAL
NORWEGIAN COMPUTING CENTER

Dialogue systems (2)

Pierre Lison
plison@nr.no

IN4080, Autumn 2025, video lecture

Week 43


- The second lecture on dialogue systems will be done **remotely**, through a series of shorter videos
- Don’t hesitate to reach out to me (plison@nr.no) or on our Discourse channel if you have any questions!

Plan:

- **Video 1: generative dialogue models**
- Video 2: dialogue management
- Video 3: system development and evaluation

Quick recap


Representation of user intent
(discrete category, embeddings from LLM, etc.)



Quick recap


Rule-based approaches

= «triggered» patterns



Quick recap


NLU approaches



Quick recap

IR approaches


(sparse or dense) *embedding*



Focus of this video

Generative approaches


*LLM embeddings (*token vectors)



Generative models


- IR models select a response among the ones found in the corpus

  ➔ In other words, they can never produce a “new” response



- An alternative is to use an LLM to **generate** the response token-by-token
  - Using an *encoder-decoder model*, like in MT, with both self-attention and cross-attention
  - Or with a *decoder-only model*, like GPT → Dominant approach nowadays (using large, pretrained LLMs)

Generation process



Input format

- The input to the generative model should include everything that is relevant for producing a correct response:
  - A **system prompt** specifying how the system should answer
  - Other **contextual information** (like the current date)
  - The **history** of previous dialogue turns (both user and system)
- *Special tokens* often used by LLMs to structure this input:

Special tokens for Llama 3.1:

```
<|begin_of_text|><|start_header_id|>system<|end_header_id|>

Cutting Knowledge Date: December 2023
Today Date: 23 July 2024


You are a helpful assistant<|eot_id|><|start_header_id|>user<|end_header_id|>

What is the capital of France?<|eot_id|><|start_header_id|>assistant<|end_header_id|>
```

External resources

- Dialogue systems often need to connect to external resources, such as:
  - *Structured databases* that can be queried and updated
  - *Web services* available through an API
  - *Sensors* and *actuators* (for robots and physical interfaces)

➔ Solution: Have the LLM produce output such as SQL queries, API or function calls



Adherence to quality criteria

- We must ensure the system responses satisfy a **number of criteria**, such as providing *informative* and *relevant* answers, not being *offensive*, not repeating *misinformation*, remaining *politically neutral*, etc.
  - The exact criteria will depend on the application
- The types of criteria to fulfill will also depend on whether the dialogue system is **task-oriented** or **open-domain**

Dialogue geared towards a specific *task* to complete (booking a flight, answering questions, conducting a tutoring lesson, etc.)

Generic dialogues without a fixed, predefined task to accomplish. Open-domain chatbots, social robots, etc.

NB: The boundary between those two types of systems is quite blurry

Adherence to quality criteria

- How to ensure our conversational system will adhere to those criteria?
- Four possible strategies:
  - **System prompts** with general guidelines
  - **Fine-tuning** on “good examples” of answers
  - **Preference optimization** from expert ratings
  - **Moderation layer** that can “flag” outputs that do not meet the criteria



Alignment with user expectations

- This alignment should also take into account how *users* expect the dialogue system to behave
- Conversational style, politeness, verbosity, turn-taking, etc.
- Can be optimised through fine-tuning on «good dialogues»
- Or by preference optimization based on user-provided preference ratings




[See e.g. Wu, A. et al, Aligning Spoken Dialogue Models from User Interactions, ICML 2025.]

Adversarial dialogues

Many users will intentionally try to “break” the dialogue system:


- Jailbreaking



Adversarial dialogues

Many users will intentionally try to “break” the dialogue system:

- Jailbreaking
- Prompt injection
- …



LLMs are also vulnerable to a wide range of attacks: backdoors, data poisoning, leakage of personal information or copyrighted material, etc.



Developers of conversational interfaces must always consider how their system may be abused or attacked

Next videos

- 2 other videos this week:
  - **Dialogue management** (including a bit of linguistics on some basic properties of human-human dialogues)
  - **System development** and **evaluation**

