– IN5550 –
Neural Methods in Natural Language Processing
Home Exam: Task Overview and Kick-Off

Andrey Kutuzov, Vladislav Mikhailov, Roxana Pop, David Samuel,

& Sondre Wold

University of Oslo

April 28th, 2025



All home exam info is on the semester page

Between Monday April 28 and Monday June 2, there will be a home exam in the form of a small research project. To pass the exam, students need to submit and have accepted a scientific paper to the 7th IN5550 Workshop on Neural Natural Language Processing (WNNLP 2025).

Background

Final examination in this class takes the form of a 'home exam', i.e. a project that students can work on over a period of three weeks. Like for the exam-qualifying obligatory assignments, group work (in teams of up to three students) is encouraged (but **PhD-students** enrolled for **IN9550** must complete the home exam **individually**). Team composition needs to be declared at the start of the exam period and, cannot be changed after April 30th, 2025. Also, each team needs to decide beforehand which of the available topics they want to research; these 'tracks' of the exam will be introduced in the lecture on April 28. Further background on the tracks and supporting data and code will be available through the course GitHub repo. Please announce your team composition and choice of track no later than April 30th by emailing the course contact address `in5550-help@ifi.uio.no`.

The main exam period will be Monday, April 28 to Tuesday, May 20, 2025. Once a team declares their track (by email, see above) they will receive a written set of suggestions for how to approach the research project. During the exam period, there will be no regular lectures or group sessions. However, project teams will be offered mentoring sessions with the track chairs (the course instructors); these sessions will be organized as a joint meeting for all teams subscribed to a given track.

https://www.uio.no/studier/emner/matnat/ifi/IN5550/v25/final-exam/

Home Exam

General Idea

- Use as guiding metaphor: Preparing a scientific paper for publication.

Home Exam

General Idea

- Use as guiding metaphor: Preparing a scientific paper for publication.

7th IN5550 Teaching Workshop on Neural NLP (WNNLP 2025)

Home Exam

General Idea

- Use as guiding metaphor: Preparing a scientific paper for publication.

7th IN5550 Teaching Workshop on Neural NLP (WNNLP 2025)

Standard Process

(0) Problem Statement

(1) Experimentation

(2) Analysis

(3) Paper Submission

(4) Reviewing

(5) Camera-Ready Manuscript

(6) Presentation

WNNLP 2025: Call for Papers

General Constraints

- Seven specialized tracks:
  - Fact verification (Roxana Pop)
  - Food hazard detection (Sondre Wold)
  - Full dependency parsing of Norwegian (David Samuel)
  - Parameter Efficient Definition Modeling (Mariia Fedorova)
  - Preference prediction and explanation (Vladislav Mikhailov)
  - Training tiny LLMs (Lucas Georges Gabriel Charpentier)
  - Unlearning sensitive content from LLMs (Andrey Kutuzov)
- Long papers: up to 8 pages (minimally 5), excluding references, in ACL Rolling Review style.
- Submitted papers must be anonymous:
  - peer reviewing is double-blind.
- Replicability: Submission backed by code repository (track chairs only).

WNNLP 2025: Important Dates

Schedule

By April 30th	Declare choice of track (and team composition)
Week 19 or 20	Track specific joint mentoring meetings
May 20	(Strict) Submission deadline for scientific papers
May 21–23	Reviewing period: Each student reviews two papers
May 27	Track Chairs announce acceptance decisions
May 30	Camera-ready papers due, with requested revisions
June 2	Oral presentations and awards at the workshop

All dates AOE (anywhere on Earth).
Submission website:
`https://openreview.net/group?id=uio.no/Univeristy_Of_Oslo/2025/WNNLP`

WNNLP 2025: Programme Committee

General Chair

- Andrey Kutuzov

Track Chairs

- Fact verification: Roxana Pop
- Food hazard detection: Sondre Wold
- Full dependency parsing of Norwegian: David Samuel
- Parameter Efficient Definition Modeling: Mariia Fedorova
- Preference prediction and explanation: Vladislav Mikhailov
- Training tiny LLMs: Lucas Georges Gabriel Charpentier
- Unlearning sensitive content from LLMs: Andrey Kutuzov

Peer Reviewers

- All students who have submitted a scientific paper

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Fact verification

Task

- Based on the FEVER workshop shared task

Fact verification

Task

- Based on the FEVER workshop shared task
- Input
  - **Claim**, eg. *"Anxiety levels among young teenagers dropped during the coronavirus pandemic, a study has suggested"*
  - Collection of **texts** that support/refute the claims
- Output
  - **label**: "Supported", "Refuted", "Not Enough Evidence", "Conflicting Evidence/Cherry-picking"
  - A textual **justification** for the system prediction

Fact verification

Resources

- AVeriTeC dataset https://fever.ai/dataset/averitec.html
  - Other options as well
- Baseline and evaluation setup https://github.com/Raldir/FEVER-8-Shared-Task
  - Including metrics for evidence evaluation

Fact verification

Directions

- Experimenting with different variations of the baseline (models)
- New architectures
- New metric?

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Food hazard detection

Goal

- Food contamination is bad.

Food hazard detection

Goal

- Food contamination is bad.
- Governmental food agencies have to monitor thousands of food recall statements.

Food hazard detection

Goal

- Food contamination is bad.
- Governmental food agencies have to monitor thousands of food recall statements.
- In this exam track, you will be working on making a classifier that categorizes food recall statements according to their hazard and product catecory.

Food hazard detection

Goal

- Food contamination is bad.
- Governmental food agencies have to monitor thousands of food recall statements.
- In this exam track, you will be working on making a classifier that categorizes food recall statements according to their hazard and product catecory.
- The exam track is based on the Food Hazard Detection Challenge from SemEval 2025.

"Randsland brand Super Salad Kit recalled due to Listeria monocytogenes"	
hazard:	listeria monocytogenes
hazard-category:	biological
product:	salads
product-category:	fruits and vegetables
"Create Common Good Recalls Jambalaya Products Due To Misbranding and Undeclared Allergens"	
hazard:	milk and products thereof
hazard-category:	allergens
product:	meat preparations
product-category:	meat, egg and dairy products

Food hazard detection

Directions

- What is the effect of data augmentation on this task?

Food hazard detection

Directions

- What is the effect of data augmentation on this task?
- The task is evaluated according to two subtasks, both of which involves predicting multiple labels. How do you make the best classification pipeline in this multi-label setup?

Food hazard detection

Directions

- What is the effect of data augmentation on this task?
- The task is evaluated according to two subtasks, both of which involves predicting multiple labels. How do you make the best classification pipeline in this multi-label setup?
- If we are constrained by runtime, what is the optimal balance between accuracy and runtime? What model fits this balance. Some researchers found SVMs to be the best!

Food hazard detection

Directions

- What is the effect of data augmentation on this task?
- The task is evaluated according to two subtasks, both of which involves predicting multiple labels. How do you make the best classification pipeline in this multi-label setup?
- If we are constrained by runtime, what is the optimal balance between accuracy and runtime? What model fits this balance. Some researchers found SVMs to be the best!
- There is a public leaderboard associated with the shared task. Can you beat current SotA results?

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Full dependency parsing of Norwegian




Figure: The full UD dependency tree of sentence “Den internasjonale domstolen har sete i Haag.”

Full dependency parsing of Norwegian

- Extension of the second obligatory assignment.
- Now you'll also have to predict the lemmas and dependency labels.
- There's also an extra language to take care of – Nynorsk – how to best use its similarities to Bokmål?
- Alternatively, you can work on a solution for the 1st UniDive Shared Task on Morphosyntactic Parsing.

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Parameter Efficient Definition Modeling

Main info

Track chairs: Mariia Fedorova

Learn more:

`https://github.uio.no/in5550/2025/tree/main/exam/defmod`

Parameter Efficient Definition Modeling

Main info

Track chairs: Mariia Fedorova

Learn more:

`https://github.uio.no/in5550/2025/tree/main/exam/defmod`

What is definition modeling?

'...da han giftet seg i 1950 livnaerte han seg og sin kone med å jakte på rype, hare og **rev**... Over 1.2 årsverk skal en normalt kunne leve av inntektene fra gardsbruket. Hva betyr **rev**?'

*'...as he married in 1950, he and his wife earned their living by hunting chicks, hare and **foxes**... After 1.2 years of work will one normally be able to live from the incomes from the use of the farm. What is the definition of **fox**?'*

Parameter Efficient Definition Modeling

After hours and hours and hours of training...



Parameter Efficient Definition Modeling

Expectation

'...da han giftet seg i 1950 livnaerte han seg og sin kone med å jakte på rype, hare og **rev**... Over 1.2 årsverk skal en normalt kunne leve av inntektene fra gardsbruket. What is the definition of rev?'
'small-to-medium-sized omnivorous mammals belonging to several genera of the family Canidae'

Parameter Efficient Definition Modeling

Expectation

'...da han giftet seg i 1950 livnaerte han seg og sin kone med å jakte på rype, hare og **rev**... Over 1.2 årsverk skal en normalt kunne leve av inntektene fra gardsbruket. What is the definition of rev?'
'small-to-medium-sized omnivorous mammals belonging to several genera of the family Canidae'

Reality

'A rabbit'

Parameter Efficient Definition Modeling

Can we at least waste less compute on that?



Parameter Efficient Definition Modeling

- Your goal: explore different PEFT methods beyond the default LoRA
- We have data for Bokmål, Nynorsk, English, German, Finnish, French, Italian, Russian and Spanish, and you can choose any
- **See more in the detailed task description on GitHub**

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Track 5: Preference prediction and explanation

Main info

Track chairs: Vladislav Mikhailov

Learn more: `https://github.uio.no/in5550/2025/tree/main/exam/preference_prediction_and_explanation`




Figure: General LLM-as-a-judge pipeline. **Source**: JudgeLM: Fine-tuned Large Language Models are Scalable Judges (Zhu et al., ICLR 2025).

Track 5: Preference prediction and explanation

Background

- Side-by-side evaluation is a well-established paradigm for assessing how well LMs align with human preferences.
- "Judge" models are widely used to mitigate the costs of human-based evaluation at scale.

Track 5: Preference prediction and explanation

Background

- Side-by-side evaluation is a well-established paradigm for assessing how well LMs align with human preferences.
- "Judge" models are widely used to mitigate the costs of human-based evaluation at scale.

LLM-as-a-judge

- Becoming more and more popular for synthetic data generation.
- Creating resources for automatically evaluating LMs, e.g.: AlpacaEval, MT-Bench-101, Chatbot Arena.

... however, this approach suffers from biases, and a fine-grained and explainable side-by-side evaluation is understudied.

Track 5: Preference prediction and explanation

Goal

- Develop self-explainable systems that can predict and explain human preferences between two language model responses.

Track 5: Preference prediction and explanation

Goal

- Develop self-explainable systems that can predict and explain human preferences between two language model responses.

Data

- The preference prediction task as part of ELOQUENT at CLEF 2025.
- 1,350 human-annotated preferences and explanations across five criteria: relevance, naturalness, truthfulness, safety, and overall quality.

Track 5: Preference prediction and explanation

Goal

- Develop self-explainable systems that can predict and explain human preferences between two language model responses.

Data

- The preference prediction task as part of ELOQUENT at CLEF 2025.
- 1,350 human-annotated preferences and explanations across five criteria: relevance, naturalness, truthfulness, safety, and overall quality.

Sub-tasks

- Preference Prediction
  - Predict which of two responses a human would prefer based on each criterion.
- Preference Prediction & Explanation
  - Predict the preferred response and generate a short explanation for why it was chosen.

Track 5: Preference prediction and explanation

General workflow

- Select a sub-task.
- Try various types of systems: (i) classification systems, (ii) generative systems, and (iii) an ensembles.
- Try various learning approaches: (i) in-context learning, (ii) finetuning, and (iii) instruction-tuning using publicly available LLMs.
- Explore approaches to generating synthetic training data and analyze the effect of the data mixtures.
- Compete against other teams and publish your exam paper!

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Training tiny LLMs

Goal

- We have only worked with already pre-trained models. It's time to train your own!
- Pre-train a LM with an architecture of your choice!

Restrictions

- The model should be trained on a single GPU in less than 24H!

Training tiny LLMs

Goal

- We have only worked with already pre-trained models. It's time to train your own!
- Pre-train a LM with an architecture of your choice!

Restrictions

- The model should be trained on a single GPU in less than 24H!
- Your imagination!

Training tiny LLMs

Data

- The BabyLM 2025 challenge data, 10M or 100M words!
- (or any dataset of your choice)

Evaluation

- After pre-training, you should fine-tune your model on an NLP dataset of your choice (we provide multiple suggestions). We also provide two datasets which can be used for additional experimentation/validation of the pre-training.

Training tiny LLMs

Data

- The BabyLM 2025 challenge data, 10M or 100M words!
- (or any dataset of your choice)

Evaluation

- After pre-training, you should fine-tune your model on an NLP dataset of your choice (we provide multiple suggestions). We also provide two datasets which can be used for additional experimentation/validation of the pre-training.
- Metric depends on which dataset you use, could be MCC, Accuracy, F1, etc.

Training tiny LLMs

Directions

- Architectural changes and innovations
- Data composition, curriculum learning etc..
- Fine-tuning dataset(s)

Training tiny LLMs

Directions

- Architectural changes and innovations
- Data composition, curriculum learning etc..
- Fine-tuning dataset(s)

You will get access to a pretty extensive codebase which contains modular code that will make the pre-training easier, but you have to code the finetuning yourself (your pre-trained model will not be a HF model).

Contents

1. Track 1: Fact verification
2. Track 2: Food hazard detection
3. Track 3: Full dependency parsing of Norwegian
4. Track 4: Parameter Efficient Definition Modeling
5. Track 5: Preference prediction and explanation
6. Track 6: Training tiny LLMs
7. Track 7: Unlearning sensitive content from LLMs

Track 7: Unlearning sensitive content from LLMs

Main info

Track chairs: Andrey Kutuzov

Learn more: `https://github.uio.no/in5550/2025/tree/main/exam/unlearning_llms`

Track 7: Unlearning sensitive content from LLMs

Main info

Track chairs: Andrey Kutuzov

Learn more: `https://github.uio.no/in5550/2025/tree/main/exam/unlearning_llms`

- A SEMEval 2025 shared task (`https://llmunlearningsemeval2025.github.io/`)
- the winners announced in February 2025, but ample room for improvement [Ramakrishna et al., 2025]
- Task: make an LLM forget or 'unlearn' some data without re-training it from scratch!
- Forget document set VS Retain document set (all in English)
- Develop a method which balances two contradictory aims.

Track 7: Unlearning sensitive content from LLMs

Models

Two OLMo-based decoder-only LLMs fine-tuned to memorize documents:

- `semeval25-unlearning-1B-model` (recommended)
- `semeval25-unlearning-7B-model` (why not?)

Both are on Fox.

Track 7: Unlearning sensitive content from LLMs

Models

Two OLMo-based decoder-only LLMs fine-tuned to memorize documents:

- `semeval25-unlearning-1B-model` (recommended)
- `semeval25-unlearning-7B-model` (why not?)


Both are on Fox.

Data

- Retain dataset (the model should retain these documents in memory)
- Forget dataset (the model should forget these documents)
- Both are on Fox, split into train and validation subsets
  1. Long form synthetic creative documents spanning different genres
  2. Short form synthetic biographies containing personally identifiable information (PII), including fake names, phone number, SSN, email and home addresses
  3. Real documents sampled from the target model's training dataset.

Track 7: Unlearning sensitive content from LLMs

Examples of full documents and test prompts for the three subtasks:



[Ramakrishna et al., 2025]

Track 7: Unlearning sensitive content from LLMs

Evaluation

- 'Regurgitation and knowledge rate' metrics:
  - Sentence completion (`rouge-L`)
  - Question answering (exact match)
- For the forget set the scores are inverted.
- The aim is to score high on both metrics for all three document types (previous slide)
- a Membership Inference Attack (MIA) score using loss based attack on a sample of member+nonmember datasets
- Performance on the MMLU benchmark [Hendrycks et al., 2020] (the model should not degrade too much!)

The official evaluation script (available and tested on Fox) aggregates all this to a single numerical score.

Track 7: Unlearning sensitive content from LLMs

Current 1B model leaderboard. Can you outperform them?

Team	Final score	Task aggregate	MIA score	MMLU
AILS-NTUA	**0.688**	**0.964**	**0.857**	0.242
SHA256	0.652	0.973	0.741	0.243
Atyaephyra	0.586	0.887	0.622	**0.248**

Track 7: Unlearning sensitive content from LLMs

Current 1B model leaderboard. Can you outperform them?

Team	Final score	Task aggregate	MIA score	MMLU
AILS-NTUA	**0.688**	**0.964**	**0.857**	0.242
SHA256	0.652	0.973	0.741	0.243
Atyaephyra	0.586	0.887	0.622	**0.248**

Approaches: Gradient Difference [Liu et al., 2022], Negative Preference Optimization [Zhang et al., 2024], and whatever else you come up with.

WNNLP 2025: What Makes a Good Scientific Paper?



Empirical (evidence-based)

- Motivate architecture choice(s) and hyper-parameters;
- systematic exploration of relevant parameter space;
- comparison to reasonable baseline or previous work.

Replicable (Reproducible)

- Everything relevant to run and reproduce in GitHub.

Analytical (Reflective)

- Identify and relate to previous work;
- explain choice of baseline or points of comparison;
- meaningful, precise discussion of results;
- 'negative' results can be interesting too;
- look at the data: discuss some examples:
- error analysis: identify remaining challenges.

References I

Hendrycks, D., Burns, C., Basart, S., Zou, A., Mazeika, M., Song, D., and Steinhardt, J. (2020).
Measuring massive multitask language understanding.
In International Conference on Learning Representations.

Liu, B., Liu, Q., and Stone, P. (2022).
Continual learning and private unlearning.
In Conference on Lifelong Learning Agents, pages 243–254. PMLR.

Ramakrishna, A., Wan, Y., Jin, X., Chang, K.-W., Bu, Z., Vinzamuri, B., Cevher, V., Hong, M., and Gupta, R. (2025).
Semeval-2025 task 4: Unlearning sensitive content from large language models.

References II


Zhang, R., Lin, L., Bai, Y., and Mei, S. (2024).
Negative preference optimization: From catastrophic collapse to effective unlearning.
In First Conference on Language Modeling.