

UNIVERSITETET I OSLO
Institutt for Informatikk

PMA

Olaf Owe, Martin Steffen



INF 4140: Models of Concurrency

Høst 2015

Mandatory assignment 2

12. Oct. 2015

Issued: 12. Oct. 2015

Due: 30. Oct. 2015

1 General remarks

How to deliver

- Your solution should be delivered online (<https://devilry.ifi.uio.no/>).
- Program examples should be commented in order to make them understandable for the group teacher or lecturer.

Who delivers

We encourage to work together in groups of 2. However, you are not allowed to solve the oblig with more than one partner. For “technical” reasons (devilry): in a group of 2 people, *both* must upload the solution (which should be identical, just the same PDF uploaded twice).¹ The solution must be marked with name(s) and email address(es) of the contributing student(s).

If in doubt, you may also read the departmental guidelines for written assignments before you start.

Check in time that devilry works and that your status within devilry (and student web etc) is ok. Don't try your INF4240-devilry access as late as the day of the deadline. In case of doubts, for clarifications, or if having trouble with devilry etc, ask us in time.

Evaluation

This assignment is graded *pass* or *fail*. You must pass the obligs in order to take the final exam.

¹That facilitates managing acceptance.

The Roller Coaster problem

Exercise 5.17 (a) in Andrews. As for the problem of the *sleeping barber*, the processes must participate in several synchronization stages. The passengers must wait for the car to be present, and the car must wait for C passengers to enter. After the ride, the car must awake all riding passengers. The solution does not have to prevent sneaking. Try to formulate a reasonable invariant based on your solution, but it is not necessary to prove the invariant using programming logic.

Greatest common divisor

Let n and m be positive integers. The following program will find the greatest common divisor $\text{gcd}(n, m)$ of n and m :

```

1
2   x := n, y := m;           // ‘input’ m and n
3
4   while (x ≠ y) {
5
6   co
7
8     < if (x > y) x:= x-y >
9
10    ||
11
12    < if (y > x) y:= y-x >
13
14  oc

```

You may assume the following properties about the greatest common divisor (gcd):

$$\begin{aligned}
 x > y &\Rightarrow \text{gcd}(x, y) = \text{gcd}(x - y, y) \\
 \text{gcd}(x, x) &= x \\
 \text{gcd}(x, y) &= \text{gcd}(y, x)
 \end{aligned}
 \tag{1}$$

Do the following:

1. Prove that the parallel program, if it terminates, has done what it is supposed to do, i.e. use *programming logic* to prove the following *post condition*

$$\{ x = \text{gcd}(n, m) \} .
 \tag{2}$$

Use

$$\text{gcd}(x, y) = \text{gcd}(n, m)
 \tag{3}$$

as *loop invariant*.

2. The program above consists of a **while** loop repeatedly executing an inner **co**-statement. This means that two processes are started and terminated each time the loop body is executed. Is it possible to develop a corresponding program with a **co** statement at the outermost level and a **while** loop in each of the processes? The program should have the same postcondition. Explain your answer. What about interference?