

Chapter 10

Code generation

Course “Compiler Construction”

Martin Steffen

Spring 2023



Chapter 10

Learning Targets of Chapter "Code generation".

1. 2AC
2. cost model
3. register allocation
4. control-flow graph
5. local liveness analysis (data flow analysis)
6. "global" liveness analysis





Chapter 10

Outline of Chapter “Code generation”.

Intro

2AC and costs of instructions

Basic blocks and control-flow graphs

Liveness analysis (general)

Local liveness: dead or alive

Local liveness^{++}: Dependence graph

Global analysis

Code generation algo



Section

Intro

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Code generation

- note: *code generation* so far: AST$^+$ to intermediate code
  - three address intermediate code (3AIC)
  - P-code
- $\Rightarrow$ *intermediate code generation*
- i.e., we are still not there ...
- material here: based on the (old) *dragon book* [2] (but principles still ok)
- there is also a new edition [1]



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Intro: code generation

- goal: translate intermediate code (= 3AI-code) to machine language
- machine language/assembler:
  - even *more* restricted
  - here: 2 address code
- limited number of *registers*
- different *address modes* with different *costs* (registers vs. main memory)

Goals

- efficient code
- small code size also desirable
- but first of all: correct code



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Code "optimization"

- often conflicting goals
- code generation: *prime* arena for achieving *efficiency*
- optimal code: undecidable anyhow (and: don't forget there's trade-offs).
- even for many more clearly defined subproblems: *untractable*

"optimization"

interpreted as: *heuristics* to achieve "good code" (without hope for *optimal* code)

- due to importance of optimization at code generation
  - time to bring out the "heavy artillery"
  - so far: all techniques (parsing, lexing, even sometimes type checking) are computationally "easy"
  - at code generation/optimization: perhaps *invest* in aggressive, computationally complex and rather advanced techniques
  - many different techniques used



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo



Section

2AC and costs of instructions

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

2-address machine code used here

- "typical" op-codes, but not a instruction set of a *concrete* machine
- two address instructions
- Note: cf. 3-address-code intermediate representation vs. 2-address machine code
  - machine code is not lower-level/closer to HW because it has one argument less than 3AC
  - it's just one illustrative choice
  - the new Dragon book: uses 3-address-machine code
- translation task from IR to 3AC or 2AC: comparable challenge



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

2-address instructions format

Format

OP source dest

- note: *order* of arguments here (esp. for minus)
- restrictions on *source* and *target*
  - register or memory cell
  - source: can additionally be a constant

```
ADD a b   // b := b + a
SUB a b   // b := b - a
MUL a b   // b := b * a
GOTO i    // unconditional jump
```

- further opcodes for conditional jumps, procedure calls ....



Side remarks: 3A machine code

Possible format

```
OP source1 source2 dest
```

- but: what's the *difference* to 3A *intermediate* code?
- apart from a more restricted instruction set:
- restriction on the operands, for example:
  - only *one* of the arguments allowed to be a memory access
  - *no fancy addressing* modes (indirect, indexed ... see later) for memory cells, only for registers
- not "too much" memory-register traffic back and forth per machine instruction
- example:

$$\&x = \&y + *z$$

may be 3A-intermediate code, but not 3A-machine code



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Cost model


- "optimization": need some well-defined "measure" of the "quality" of the produced code
- interested here in *execution* time
- not all instructions take the same time
- estimation of execution
- factors outside our control/not part of the cost model: effect of *caching*

cost factors:

- *size* of instruction
  - it's here not about code size, but
  - instructions need to be *loaded*
  - longer instructions $\Rightarrow$ perhaps longer load
- address modes (as *additional costs*: see later)
  - registers vs. main memory vs. constants
  - direct vs. indirect, or indexed access



Instruction modes and additional costs



Modes and cost model

mode	abbr.	address	**added cost**	
absolute	M	M	1	
register	R	R	0	
indexed	c(R)	$c + cont(R)$	1	
indirect register	*R	$cont(R)$	0	
indirect indexed	*c(R)	$cont(c + cont(R))$	1	
literal	$\#M$	the *value* M	1	only for source

- indirect: useful for elements in "records" with known off-set
- indexed: useful for slots in arrays

Examples a := b + c

Using registers (costs=6)

```
MOV b, R0   // R0 = b
ADD c, R0   // R0 = c + R0
MOV R0, a   // a = R0
```

Mem.-mem. ops (costs=6)

```
MOV b, a    // a = b
ADD c, a    // a = c + a
```

Addresses in registers (costs=2)

```
MOV *R1, *R0 // *R0 = *R1
ADD *R2, *R1 // *R1 = *R2 +
```

Assume `R0`, `R1`, and `R2` contain *addresses* for `a`, `b`, and `c`

Storing back to mem. (costs=3)

```
ADD R2, R1   // R1 = R2 + R1
MOV R1, a    // a = R1
```

Assume `R1` and `R2` contain *values* for `b`, and `c`





Section

Basic blocks and control-flow graphs

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Basic blocks

- machine code level equivalent of straight-line code
- (a largest possible) sequence of instructions without
  - jump out
  - jump in
- elementary unit of code analysis/optimization[1]
- amenable to analysis techniques like
  - static simulation/symbolic evaluation
  - abstract interpretation
- basic unit of code generation

[1] Those techniques can also be used across basic blocks, but then they become more costly and challenging.



Control-flow graphs

CFG

basically: *graph* with

- nodes = basic blocks
- edges = (potential) jumps (and "fall-throughs")

- here (as often): CFG on 3AIC (linear intermediate code)
- also possible CFG on low-level code,
- or also:
  - CFG extracted from AST[2]
  - here: the opposite: synthesizing a CFG from the linear code
- explicit data structure (as another intermediate representation) or implicit only.

[2] See also the exam 2016.



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

From 3AC to CFG: "partitioning algo"

- remember: 3AIC contains *labels* and (conditional) jumps

$\Rightarrow$ algo rather straightforward

- the only complication: some labels can be ignored
- we ignore procedure/method calls here
- concept: "leader" representing the nodes/basic blocks

Leader

- first line is a leader
- $\mathbf{GOTO}\, i$: line labelled i is a leader
- instruction *after* a $\mathbf{GOTO}$ is a leader

Basic block

instruction sequence from (and including) one leader to (but excluding) the next leader or to the end of code



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Partitioning algo

```
    ..............
    ..............
    ..............
    if ... goto L5
L1  ..............
L2  ..............
    ..............
    ..............
    goto L3
L5  ..............
    ..............
L3  ..............
    ..............
    if ... goto L1
    ..............
    goto L3
```



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Partitioning algo

```
    ..............
    ..............
    ..............
    if ... goto L5
L1  ..............
L2  ..............
    ..............
    ..............
    goto L3
L5  ..............
    ..............
L3  ..............
    ..............
    if ... goto L1
    ..............
    goto L3
```

- note: no line jumps to L_2



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo


3AIC for factorial (from previous chapter)

```
read x
t1 = x > 0
if_false t1 goto L1
fact = 1
label L2
t2 = fact * x
fact = t2
t3 = x - 1
x = t3
t4 = x == 0
if_false t4 goto L2
write fact
label L1
halt
```



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Factorial: CFG



- goto/conditional goto: never *inside* block
- not every block
  - ends in a goto
  - starts with a label
- ignored here: function/method calls, i.e., focus on
- *intra-procedural* cfg



Levels of analysis

- here: *three* levels where to apply code analysis / optimizations

levels

1. local: per basic block (block-level)
2. global: per function body/intra-procedural CFG
3. (inter-procedural: really global, whole-program analysis)

- better terminology: block-local, procedure-local etc.
- the "more global", the more *costly* the analysis and, especially the optimization (if done at all)



Loops in CFGs

- *loop optimization*: "loops" are thankful places for optimizations
- important for analysis to *detect* loops (in the cfg)
- importance of *loop discovery*: not too important any longer in modern languages.

Loops in a CFG vs. graph cycles

- concept of loops in CFGs not identical with cycles in a graph
- all loops are graph cycles but not vice versa

- intuitively: loops are cycles originating from source-level looping constructs ("while")
- goto's may lead to non-loop cycles in the CFG
- importance of loops: loops are "well-behaved" when considering certain optimizations/code transformations (goto's can destroy that...)



Loops in CFGs

Loop L with header h

Loop L in a CFG: set of nodes, including header node $h \in L$:


1. any node in L: a path in L to h
2. a path in L from h to any node in L
3. every edge that goes from outside L into L passes through h

often additional assumption/condition: "root" node of a CFG (there's only one) is *not* itself an entry of a loop




Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Loop example




- Loops:
  - $\{B_3, B_4\}$ (nested)
  - $\{B_4, B_3, B_1, B_5, B_2\}$
- Non-loop:
  - $\{B_1, B_2, B_5\}$
- unique entry marked red


Loop non-examples



(a)



(b)



(c)

Loops as fertile ground for optimizations

```
while (i < n) {i++; A[i] = 3*k }
```

- possible optimizations
  - move `3*k` "out" of the loop
  - put frequently used variables into *registers* while in the loop (like i)
- when moving out computation from the loop:
- put it "right in front of the loop"

$\Rightarrow$ add extra node/basic block in front of the *entry* of the loop[3]

[3] That's one of the motivations for unique entry.



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Data flow analysis in general

- general *analysis technique* working on CFGs
- many concrete forms of analyses
- such analyses: basis for (many) *optimizations*
- *data*: info stored in memory/temporaries/registers etc.
- *control*:
  - movement of the instruction pointer
  - abstractly represented by the CFG
    - inside elementary blocks: increment of the instruction pointer
    - edges of the CFG: (conditional) jumps
    - jumps together with RTE and calling convention

Data flowing from (a) to (b)

Given the control flow (normally as CFG): is it *possible* or is it *guaranteed* ("may" vs. "must" analysis) that some "data" originating at one control-flow point (a) reaches control flow point (b).



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Data flow as abstraction

- data flow analysis DFA: fundamental and important *static* analysis technique
- it's impossible to decide statically if data from (a) *actually* "flows to" (b)

$\Rightarrow$ approximative (= abstraction)

- therefore: work on the CFG: if there are two options/outgoing edges: *consider both*
- Data-flow answers therefore approximatively
  - if it's *possible* that the data flows from (a) to (b)
  - it's *neccessary* or unavoidable that data flows from (a) to (b)
- for *basic blocks*: exact answers possible





Section

Liveness analysis (general)

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Data flow analysis: Liveness

- prototypical / important data flow analysis
- especially important for register allocation

Basic question

When (at which control-flow point) can I be *sure* that I don't need the current content of a variable (temporary, register) any more?

- optimization: if not needed for sure in the future: register can be used otherwise

Definition (Live)

A "variable" is live at a given control-flow point if there *exists* an execution starting from there (given the level of abstraction), where the current content of the variable is *used* in the future.



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Definitions and uses of variables

- "variables": also temporary variables are meant.
- basic notions underlying most data-flow analyses (including liveness analysis)
- here: def's and uses of *variables* (or temporaries etc.)
- all data, including intermediate results, has to be stored somewhere, in variables, temporaries, etc.

Def's and uses


- a "definition" of x = assignment to x (store to x)
- a "use" of x: read content of x (load x)

- variables can occur more than once, so
- a definition/use refers to *instances* or *occurrences* of variables ("use of x in line l " or "use of x in block b ")
- same for liveness: "x is live here, but not there"



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Defs, uses, and liveness



- x is "defined" (= assigned to) in 0, 3, and 4
- u is live "in" (= at the end of) block 2, as it *may* be *used* in 3
- a *non-live* variable at some point: "dead", which means: the corresponding memory can be reclaimed
- *note*: here, liveness across block-boundaries = "global" (but blocks contain only one instruction here)



Def-use or use-def analysis

- use-def: given a "use": determine all possible "definitions"
- def-use: given a "def": determine all possible "uses"
- for straight-line-code/inside one basic block
  - deterministic: each line has has exactly one place where a given variable has been assigned to last (or else not assigned to in the block). Equivalently for uses.
- for whole CFG:
  - approximative ("may be used in the future")
  - more advanced techiques (caused by presence of loops/cycles)
- def-use analysis:
  - closely connected to liveness analysis (basically the same)
  - *prototypical* data-flow question (same for use-def analysis), related to many data-flow analyses (but not all)



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Calculation of def/uses (or liveness . . .)

- three levels of complication
  1. inside basic block
  2. branching (but no loops)
  3. Loops
  4. [even more complex: inter-procedural analysis]

For SLC/inside basic block

- deterministic result
- simple "one-pass" treatment enough
- similar to "static simulation"

For whole CFG

- *iterative* algo needed
- dealing with non-determinism: over-approximation
- "closure" algorithms, similar to the way e.g., dealing with *first* and *follow* sets
- = fix-point algorithms





Section

Local liveness: dead or alive

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Inside one block: optimizing use of temporaries

- simple setting: *intra*-block analysis & optimization, only
- temporaries:
  - symbolic representations to hold intermediate results
  - generated on request, assuming unbounded numbers
  - intention: use registers
- limited about of register available (platform dependent)

Assumption about temps (here)

- temp's *don't transfer* data across blocks ($\neq$ program var's)


$\Rightarrow$ temp's *dead* at the beginning and at the end of a block


- but: variables have to be *assumed* live at the end of a block (block-local analysis, only)



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Forward vs backward





Intra-block liveness

```
t1 := a - b
t2 := t1 * a
a  := t1 * t2
t1 := t1 - c
a  := t1 * a
```

- let's call operand: variables or temp's
- neither temp's nor vars in the example are "single assignment",
- but first occurrence of a temp in a block: a definition (but for temps it would often be the case, anyhow)
- uses of operands: on the rhs's, definitions on the lhs's
- not good enough to say "t_1 is live in line 4" (why?)



Single step per line: transfer function

- liveness-status of an operand: *different* from lhs vs. rhs in a given instruction
- informal definition: an operand is live at some occurrence, if its content is used some place in the future

Definition (consider statement $x_1 := x_2 \ op \ x_3$)

- Variable x is live at the *beginning* of $x_1 := x_2 \ op \ x_3$, if
  1. if x is x_2 or x_3, or
  2. if x live at its *end*, if x and x_1 are different variables
- A variable x is live at the *end* of an instruction,
  - if it's live at *beginning of the next* instruction
  - if no next instruction
    - temp's are dead
    - user-level variables are (assumed) live



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Algo: dead or alive (binary info)

```
// ------ initialise T  ------------------------------------------
   for all entries: T[i,x] := D
   except: for all variables a // but not temps
               T[n,a] := L,
//---------- backward pass ------------------------------------------
for instruction i =  n-1 down to 0
    let current instruction at i+1: x := y op z;
       T[i,o] := T[i+1,o] (for all other vars o)
       T[i,x] := D // note order; x can ``equal'' y or z
       T[i,y] := L
       T[i,z] := L
end
```



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Algo: dead or alive (binary info) (2)

- Data structure T: table, mapping for each line/instruction i and variable: boolean status of "live"/"dead"
- represents liveness status per variable *at the end (i.e. rhs)* of that line
- basic block: n instructions, from 1 until n, where "line 0" represents the "sentry" imaginary line "before" the first line (no instruction in line 0)
- *backward scan* through instructions/lines from n to 0



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Run of of the algo

line	a	b	c	t_1	t_2
[0]	L	L	L	D	D
1	L	L	L	L	D
2	D	L	L	L	L
3	L	L	L	L	D
4	L	L	L	L	D
5	L	L	L	D	D

Table: Liveness analysis example: result of the analysis



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo



Section

Local liveness^{++}: Dependence graph

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Adding information: next-use

- more refined information
- not just binary dead-or-alive but next-use info

$\Rightarrow$ three kinds of information

1. Dead: D
2. Live:
   - with *local* line number of *next use*: $L(n)$
   - *potential* use of outside local basic block $L(\perp)$

- otherwise: same algo




Algo: alive with next use

```
// ------ initialise T ------------------------------------------
   for all entries: T[i,x] := D
   except: for all variables a // but not temps
                T[n,a] := L(⊥),
//---------- backward pass ------------------------------------------
for instruction i = n−1 down to 0
    let current instruction at i+1: x := y op z;
        T[i,o] := T[i+1,o] (for all other vars o)
        T[i,x] := D // note order; x can ``equal'' y or z
        T[i,y] := L(i+1)
        T[i,z] := L(i+1)
end
```



Run of the algo

line	a	b	c	t_1	t_2
[0]	$L(1)$	$L(1)$	$L(4)$	D	D
1	$L(2)$	$L(\perp)$	$L(4)$	$L(2)$	D
2	D	$L(\perp)$	$L(4)$	$L(3)$	$L(3)$
3	$L(5)$	$L(\perp)$	$L(4)$	$L(4)$	D
4	$L(5)$	$L(\perp)$	$L(\perp)$	$L(5)$	D
5	$L(\perp)$	$L(\perp)$	$L(\perp)$	D	D




```
1  t1 := a - b
2  t2 := t1 * a
3  a  := t1 * t2
4  t1 := t1 - c
5  a  := t1 * a
```

Dependency graph and def-use

- small step from **next**-use of **all**-future-uses

Def-use analysis


Connect definitions with all their uses ⇒ dependency graph

- straight-line code
- acyclic graph ⇒ DAG (or partial order)
- nodes: (lines of) instructions (or variable instance)



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

DAG of the block





```
1  t1 := a - b
2  t2 := t1 * a
3  a  := t1 * t2
4  t1 := t1 - c
5  a  := t1 * a
```



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

DAG of the block




- no linear order (as in code), only *partial order*
- *the* next use: meaningless
- but: *all "next" uses* visible
- node = occurrence of a variable
- e.g.: node 1 for "defining" t_1 has *three* uses
- different "versions" (instances) of t_1




Dependence graphs for pure expressions


```
t1 :=   2 * z
t2 :=   x + t1
t3 :=   a + b
 x :=  t2 - t3
```



Dependence graphs for pure expressions: cf. AST!

```
t1 :=   2 * z
t2 :=   x + t1
t3 :=   a + b
 x :=  t2 - t3
```





(S)SA format

```
t1 := a - b
t2 := t1 * a
a  := t1 * t2
t1 := t1 - c
a  := t1 * a
```




Figure: DAG for the 3AIC code block



(S)SA format

```
t1 := a0 - b0
t2 := t1 * a0
a1 := t1 * t2
t3 := t1 - c0
a2 := t3 * a1
```




Figure: DAG for the 3AIC code block



Section

Global analysis

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Global data flow analysis

- block-local
  - block-local analysis (here liveness): *exact* information possible
  - block-local liveness: *1 backward scan*
  - important use of liveness: *register allocation*, temporaries typically don't survive blocks anyway
- global: working on complete CFG

2 complications

- branching: *non-determinism*, unclear which branch is taken
- loops in the program (loops/cycles in the graph): simple *one pass* through the graph does not cut it any longer

- *exact* answers no longer possible (undecidable)

$\Rightarrow$ work with safe approximations

- this is: general characteristic of DFA



Generalizing block-local liveness analysis

- *assumptions* for block-local analysis
  - all program variables (assumed) *live* at the end of each basic block
  - all temps are assumed *dead* there.
- now: we do better, info across blocks

at the end of each block:

which variables may be used in subsequent block(s).

- now: re-use of temporaries (and thus corresponding registers) across blocks possible
- remember local liveness algo: determined liveness status per var/temp *at the end* of each "line/instruction"



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Connecting blocks in the CFG: *inLive* and *outLive*

- CFG:
  - pretty conventional graph (nodes and edges, often designated start and end node)
  - *nodes* = basic blocks = contain straight-line code (here 3AIC)
  - being conventional graphs:
    - conventional representations possible
    - E.g. nodes with lists/sets/collections of immediate *successor nodes* plus immediate *predecessor nodes*
- remember: local liveness status
  - can be different *before* and *after* one single instruction
  - liveness status *before* expressed as dependent on status *after*

  $\Rightarrow$ backward scan
- Now per block: *inLive* and *outLive*



$inLive$ and $outLive$

- tracing / approximating set of live variables[4] at the *beginning* and *end* per basic block
- $inLive$ of a block: depends on
  - $outLive$ of that block and
  - the SLC inside that block
- $outLive$ of a block: depends on $inLive$ of the *successor* blocks

Approximation: To err on the safe side

Judging a variable (statically) live: always *safe*. Judging wrongly a variable *dead* (which actually will be used): unsafe


- goal: smallest (but safe) possible sets for $outLive$ (and $inLive$)

[4] To stress "approximation": $inLive$ and $outLive$ contain sets of *statically* live variables. If those are dynamically live or not is undecidable.



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Example: factorial CFG



- $inLive$ and $outLive$
- picture shows arrows as *successor nodes*
- needed *predecessor nodes* (reverse arrows)

node/block	predecessors
B_1	$\emptyset$
B_2	$\{B_1\}$
B_3	$\{B_2, B_3\}$
B_4	$\{B_3\}$
B_5	$\{B_1, B_4\}$

Block local info for global liveness/data flow analysis

- 1 CFG per procedure/function/method
- as for SLC: algo works backwards
- for each block: underlying block-local liveness analysis

3-valued block local status per variable

result of block-local live variable analysis

1. *locally live* on entry: variable used (before overwritten)
2. *locally dead* on entry: variable overwritten (before used)
3. status not locally determined: variable neither assigned to nor read locally

- for efficiency: **precompute** this info, before starting the global iteration $\Rightarrow$ avoid *recomputation* for blocks in loops



Global DFA as iterative "completion algorithm"

- different names for the general approach
  - *closure* algorithm, *saturation* algo
  - *fixpoint* iteration
- basically: a big loop with
  - iterating a step approaching an intended solution by making current approximation of the solution *larger*
  - until the solution stabilizes
- similar (for example): calculation of first- and follow-sets
- often: realized as *worklist algo*
  - named after central data-structure containing the "work-still-to-be-done"
  - here possible: worklist containing nodes untreated wrt. liveness analysis (or DFA in general)



Example

```
     a := 5
L1:  x := 8
     y := a + x
     if_true x=0 goto L4
     z := a + x          // B3
     a := y + z
     if_false a=0  goto L1
     a := a + 1          // B2
     y := 3 + x
L5   a := x + y
     result := a + z
     return result       // B6
L4:  a := y + 8
     y := 3
     goto L5
```



Targets & Outline

Intro

2AC and costs of instructions

Basic blocks and control-flow graphs

Liveness analysis (general)


Local liveness: dead or alive

Local liveness^{++}: Dependence graph

Global analysis

Code generation algo

CFG: initialization



- $inLive$ and $outLive$: *initialized* to $\emptyset$ everywere
- note: start with (most) *unsafe* estimation
- extra (return) node
- but: analysis here *local per procedure*, only

Iterative algo

General schema

Initialization start with the "minimal" estimation ($\emptyset$ everywhere)

Loop pick one node & update (= enlarge) liveness estimation in connection with that node


Until finish upon stabilization (= no further enlargement)

- order of treatment of nodes: in principle arbitrary[5]
- in tendency: following edges backwards
- comparison: for linear graphs (like inside a block):
  - no repeat-until-stabilize loop needed
  - 1 simple backward scan enough


[5] There may be more efficient and less efficient orders of treatment.



Liveness: run




Liveness: run







Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run




Liveness: run



Liveness: run



Liveness: run



Liveness example: remarks

- the shown traversal strategy is (cleverly) backwards
- example resp. example run simplistic:
- the *loop* (and the choice of "evaluation" order):

"harmless loop"


after having updated the $outLive$ info for B_1 following the edge from B_3 to B_1 *backwards* (propagating flow from B_1 back to B_3) does not increase the current solution for B_3

- no need (in this particular order) for continuing the iterative search for stabilization
- in other examples: loop iteration cannot be avoided
- note also: end result (after stabilization) independent from evaluation order! (only some strategies may stabilize faster...)




Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo


Another, more interesting, example




Another, more interesting, example




Another, more interesting, example



Another, more interesting, example




Another, more interesting, example







Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example




Another, more interesting, example



Another, more interesting, example



Another, more interesting, example



Example remarks

- loop: this time: updating estimation more than once
- evaluation order not chosen ideally (but it's not generally solvable)



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Precomputing the block-local "liveness effects"

- *precomputation* of the relevant info: efficiency
- traditionally: represented as *kill* and *generate* information
- here (for liveness)
  1. kill: variable instances, which are overwritten
  2. generate: variables used in the block (before overwritten)
  3. rests: all other variables won't change their status


Constraint per basic block (transfer function)

$$inLive = outLive \backslash kill(B) \cup generate(B)$$


- note:
  - order of kill and generate in above's equation
  - a variable killed in a block may be "revived" in a block
- simplest (one line) example: `x := x +1`



Example once again: kill and gen




Example once again: kill and gen






Example once again: kill and gen






Example once again: kill and gen




Example once again: kill and gen






Example once again: kill and gen






Example once again: kill and gen






Example once again: kill and gen







Example once again: kill and gen



Example once again: kill and gen




Example once again: kill and gen






Example once again: kill and gen






Example once again: kill and gen






Example once again: kill and gen




Example once again: kill and gen






Example once again: kill and gen



Example once again: kill and gen





Section

Code generation algo

Chapter 10 “Code generation”
Course “Compiler Construction”
Martin Steffen
Spring 2023

Simple code generation algo

- simple algo: *intra-block* code generation
- core problem: register use
- register allocation & assignment
- hold calculated values in registers longest possible
- intra-block only $\Rightarrow$ at exit:
  - all *variables* stored back to main memory
  - all temps assumed "lost"
- remember: assumptions in the intra-block liveness analysis



Limitations of the code generation

- local intra block:
  - no analysis across blocks
  - no procedure calls, etc.
- no complex data structures
  - arrays
  - pointers
  - ...

some limitations on how the algo itself works for one block

- for read-only variables: never put in registers, even if variable is *repeatedly* read
  - algo works only with the temps/variables given and does not come up with new ones
  - for instance: DAGs could help
- no *semantics* considered
  - like *commutativity*: $a + b$ equals $b + a$



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Purpose and "signature" of the *getreg* function

- one *core* of the code generation algo
- simple code-generation here $\Rightarrow$ simple *getreg*

getreg function

available: *liveness/next-use* info

Input: TAIC-instruction $x := y \ \mathbf{op} \ z$

Output: return *location* where x is to be stored

- location: register (if possible) or memory location



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Code generation invariant

it should go without saying . . . :

Basic safety invariant

At each point, "live" variables (with or without next use in the current block) must exist in at least one location

- another invariant: the location returned by getreg: the one where the result of a 3AIC assignment ends up



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Register and address descriptors

- code generation/$getreg$: keep track of
  1. register contents
  2. addresses for names

Register descriptor

- tracking current "content" of reg's (if any)
- consulted when new reg needed
- as said: at block entry, assume all regs unused

Address descriptor

- tracking location(s) where current value of name can be found
- possible locations: register, stack location, main memory
- >1 location possible (but not due to over-approximation, exact tracking)



Code generation algo for $x := y$ op z

1. determine location (preferably register) for result

```
l = getreg( ``x := y op z'')
```

2. make sure, that the value of y is in l :
   - consult address descriptor for $y \Rightarrow$ current locations l_y for y
   - choose the best location l_y from those (preferably register)
   - if value of y *not* in l, generate

```
MOV l_y , l
```

3. generate

```
OP l_z , l // l_z: a current location of z (prefer reg's)
```

   - update address descriptor $[x \mapsto_{\cup} l]$
   - if l is a reg: update reg descriptor $l \mapsto x$

4. exploit liveness/next use info: update register descriptors

Skeleton code generation algo for $x := y \text{ op } z$

```
l = getreg(``x:= y op z'') // target location for x
if l ∉ T_a(y) then let l_y ∈ T_a(y)) in emit ("MOV l_y, l");
let l_z ∈ T_a(z) in emit ("OP l_z,l");
```

- "skeleton"
  - *nondeterministic*: we ignored how to choose l_z and l_y
  - we ignore *bookkeeping* in the *name* and *address* descriptor tables ($\Rightarrow$ step 4 also missing)
  - details of $getreg$ hidden.



```
l = getreg(``x:= y op z'') // generate target location for x
if l ∉ T_a(y)
then let l_y ∈ T_a(y)) // pick a location for y
       in  emit (MOV l_y , l)
else skip;
let l_z ∈ T_a(z) in emit ("OP l_z , l ");
T_a := T_a[x ↦∪ l];
if   l is a register
then T_r := T_r[l ↦ x]
```



Targets & Outline

Intro

2AC and costs of instructions

Basic blocks and control-flow graphs

Liveness analysis (general)

Local liveness: dead or alive

Local liveness^{++}: Dependence graph

Global analysis

Code generation algo

Exploit liveness/next use info: recycling registers

- register descriptors: don't update themselves during code generation
- once set (e.g. as $R_0 \mapsto t$), the info stays, unless reset
- thus in step 4 for $z := x \ \mathbf{op} \ y$:



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Code generation algo for $x := y$ op z

```
l = getreg("i: x := y op z")   // i for instructions line number/label
if l ∉ T_a(y)
then let l_y = best (T_a(y))
       in  emit ("MOV l_y, l")
else skip;
let l_z = best (T_a(z))
in emit ("OP l_z,l");
T_a := T_a\(_ ↦ l);
T_a := T_a[x ↦ l];
if   l is a register
then T_r := T_r[l ↦ x];

if   ¬T_live[i,y] and T_a(y) = r then T_r := T_r\(r ↦ y)
if   ¬T_live[i,z] and T_a(z) = r then T_r := T_r\(r ↦ z)
```

Updating and exploit liveness info by recycling reg's

if y and/or z are currently

- *not live* and are
- in *registers*,

$\Rightarrow$ "wipe" the info from the corresponding register descriptors

getreg algo: $x := y$ op z

- goal: return a location for x
- basically: check possibilities of register uses
- starting with the "cheapest" option

Do the following steps, in that order

1. **in place:** if x is in a register already (and if that's fine otherwise), then return the register
2. **new register:** if there's an unused register: return that
3. **purge filled register:** choose more or less cleverly a filled register and save its content, if needed, and return that register
4. **use main memory:** if all else fails



getreg algo: $x := y$ op z in more details

1. if
   - y in register R
   - R holds *no alternative names*
   - y is *not live* and has no next use after the 3AIC instruction
   - $\Rightarrow$ return R
2. else: if there is an empty register R': return R'
3. else: if
   - x has a next use [or operator requires a register] $\Rightarrow$
     - find an occupied register R
     - store R into M if needed (MOV R, M))
     - don't forget to update M 's address descriptor, if needed
     - return R
4. else: x not used in the block *or* no suitable occupied register can be found
   - return x as location l

- choice of purged register: *heuristics*
- remember (for step 3): registers may contain value for > 1 variable $\Rightarrow$ *multiple* MOV's



Sample TAIC

```
d := (a-b) + (a-c) + (a-c)
```

```
t := a − b
u := a − c
v := t + u
d := v + u
```

line	a	b	c	d	t	u	v
[0]	$L(1)$	$L(1)$	$L(2)$	D	D	D	D
1	$L(2)$	$L(\perp)$	$L(2)$	D	$L(3)$	D	D
2	$L(\perp)$	$L(\perp)$	$L(\perp)$	D	$L(3)$	$L(3)$	D
3	$L(\perp)$	$L(\perp)$	$L(\perp)$	D	D	$L(4)$	$L(4)$
4	$L(\perp)$	$L(\perp)$	$L(\perp)$	$L(\perp)$	D	D	D



Targets & Outline
Intro
2AC and costs of instructions
Basic blocks and control-flow graphs
Liveness analysis (general)
Local liveness: dead or alive
Local liveness^{++}: Dependence graph
Global analysis
Code generation algo

Code sequence

	3AIC	2AC	reg. descr.		addr. descriptor						
			R_0	R_1	a	b	c	d	t	u	v
[0]			$\perp$	$\perp$	a	b	c	d	t	u	v
1	t := a − b	**MOV** a, R0	$[a]$		$[R_0]$						
		SUB b, R0	t		~~R_0~~				R_0		
2	u := a − c	**MOV** a, R1	·	$[a]$	$[R_0]$						
		SUB c, R1		u	~~R_0~~					R_1	
3	v := t + u	**ADD** R1, R0	v	·					~~R_0~~		R_0
4	d := v + u	**ADD** R1, R0	d					R_0			~~R_0~~
		MOV R0, d									
			R_i: unused		all var's in "home position"						

- address descr's: "home position" not explicitly needed.
- e.g. variable a to be found "at a " (if not stale), as indicated in line "0".
- in the table: only *changes* (from top to bottom) indicated
- after line 3:
  - t dead
  - t resides in R_0 (and nothing else in R_0)

  $\rightarrow$ reuse R_0
- Remark: info in [brackets]: "ephemeral"



References I



Targets & Outline

Intro

2AC and costs of instructions

Basic blocks and control-flow graphs

Liveness analysis (general)

Local liveness: dead or alive

Local liveness^{++}: Dependence graph

Global analysis

Code generation algo

Bibliography

[1] Aho, A. V., Lam, M. S., Sethi, R., and Ullman, J. D. (2007). *Compilers: Principles, Techniques and Tools*. Pearson,Addison-Wesley, second edition.

[2] Aho, A. V., Sethi, R., and Ullman, J. D. (1986). *Compilers: Principles, Techniques, and Tools*. Addison-Wesley.